Pathway Enrichment Based on Text Mining and Its Validation on Carotenoid and Vitamin A Metabolism

Andra Waagmeester,^{1,2,3} Piotr Pezik,¹ Susan Coort,³ Franck Tourniaire,⁴
Chris Evelo,³ and Dietrich Rebholz-Schuhmann¹

Abstract

Carotenoid metabolism is relevant to the prevention of various diseases. Although the main actors in this metabolic pathway are known, our understanding of the pathway is still incomplete. The information on the carotenoids is scattered in the large and growing body of scientific literature. We designed a text-mining work flow to enrich existing pathways. It has been validated on the vitamin A pathway, which is a well-studied part of the carotenoid metabolism. In this study we used the vitamin A metabolism pathway as it has been described by an expert team on carotenoid metabolism from the European network of excellence in Nutrigenomics (NuGO). This work flow uses an initial set of publications cited in a review paper (1,191 publications), enlarges this corpus with Medline abstracts (13,579 documents), and then extracts the key terminology from all relevant publications. Domain experts validated the intermediate and final results of our text-mining work flow. With our approach we were able to enrich the pathway representing vitamin A metabolism. We found 37 new and relevant terms from a total of 89,086 terms, which have been qualified for inclusion in the analyzed pathway. These 37 terms have been assessed manually and as a result 13 new terms were then added as entities to the pathway. Another 14 entities belonged to other pathways, which could form the link of these pathways with the vitamin A pathway. The remaining 10 terms were classified as biomarkers or nutrients. Automatic literature analysis improves the enrichment of pathways with entities already described in the scientific literature.

Introduction

CAROTENOIDS ARE NATURAL nutritional compounds. Fruits, vegetables and derived products constitute the major sources of these lipid-soluble pigments. There is strong evidence that high dietary intake of these compounds is beneficial for humans, and that it is associated with a lower risk of developing cardiovascular diseases, cancers, and age-related eye diseases (Amiot-Carlin, 2008; Bendich and Olson, 1989; Krinsky, 1993). Several mechanisms have been described that explain at least in part the observed effects. Examples include: (1) a role in the scavenging of free radicals, (2) the enhancement of gap-junction communication, (3) a role in immunomodulation, (4) reduction of the risk of site-specific cancer and heart disease, and (5) the protection of eye tissue (Yeum and Russell, 2002). Among the more than 600 identified carotenoids, around 10% are categorized as pro-vitamin A, meaning that they can be cleaved by the organism to

produce retinal, the precursor of vitamin A (retinol). Harrison (2005) estimated in 2005 that more than 100 million children worldwide suffer from vitamin A deficiency, and indicated that an increased understanding of the metabolic processes concerning the absorption of carotenoids could lead to better nutrition and thereby in general to an increase in the health of several populations. Getting a profound understanding of the metabolic pathway of carotenoid metabolism is assisted by the integration of a variety of study results from different sources and biomedical research domains (Voutilainen et al., 2006).

Pathways are abstract and functional representations of biological knowledge (Cary et al., 2005). Our understanding of their functioning is essential in the analysis of genomic results (Dahlquist et al., 2002) and, because such an approach requires accurate and up-to-date representations of pathways, this research work is ongoing. For the creation of such representations the scientific curators (biologists and other

¹European Bioinformatics Institute, Hinxton, Cambridge, CB10 1SD United Kingdom.

²Maastricht ICT Competence Centre, Maastricht University, Maastricht, The Netherlands.

³Department of Bioinformatics, BiGCaT, Maastricht University, Maastricht, The Netherlands.

⁴Human Nutrition Research Centre, University of Newcastle upon Tyne, Faculty of SAgE, Newcastle upon Tyne, United Kingdom.

domain experts) merge their expert knowledge with information from biological databases (Bader et al., 2006), and available scientific literature.

In biology, the Medline database is the primary resource of scientific literature. It contains more than 18 million references to scientific journal publications in the biomedical field, including author information and abstracts. The rate of growth of Medline is so high that scientists have big difficulties to keep up to date (Jensen et al., 2006). New approaches to filter information from the scientific literature are required. Traditional procedures for gathering documents from a corpus (i.e., a collection of documents. PubMed could be considered as a corpus of biomedical abstracts) rely on selecting a set of appropriate key words with which one hopes to retrieve as many relevant publications as possible from the document collection at hand. Measures have been defined to monitor and optimize the retrieval for a given task to the selection of relevant documents (Jensen et al., 2006). Whenever the resulting set of references is too overwhelming, one coping strategy is to limit the search to review articles. To this end, PubMed, the Web-based interface to Medline, offers functionality to limit the searches to retrieve only reviews. By manually selecting appropriate reviews scientists acquire references to other relevant articles.

A literature search is optimal if both precision and recall are high. Precision is the number of relevant documents in all retrieved documents. Recall is the portion of retrieved documents out of all relevant documents in the corpus (Shatkay and Feldman, 2003). In other words, the recall is the ratio between the true positives and the sum of the true positives and the false negatives. The precision is the ratio between the true positives and the sum of the true positives and the false positives. A literature search is optimal if the results are generated with high recall and high precision at the same time, which is difficult to achieve because often high precision hinders high recall and vice versa (see the explanations below).

Two factors have a strong influence on recall and precision. The first factor is the polysemy (a term denoting multiple meanings) of key words used in user queries leading to their ambiguous interpretation in the text. Highly ambiguous terms decrease precision, because the number of false positives could increase, that is, the more senses a term has the more diverse the final retrieval of documents (e.g., the term cancer denoting a disease and a species). The second factor is synonymy (the use of different terms to denote the same concept). If a concept is represented by more than one term, and neither the query system nor the user formulating the query considers all relevant synonyms to generate a complete query, this changes the recall due to the potential increase of false negatives. An example that illustrates the influence of the latter factor is the retrieval of documents describing MRI (magnetic resonance imaging) (Spasic et al., 2008). This imaging method is widely used in medicine. The same underlying physical method is used in chemistry for spectral analyses, but is here called NMR (nuclear magnetic resonance). Documents describing NMR could be relevant for someone interested in MRI. Unawareness of synonymous terms leads to missing relevant literature. PubMed uses thesauri like MESH to overcome some of these problems. The link between NMR and MRI will be found in MESH. But synonymy could be so subtle that it would require very big thesauri, and then again

the excessive use of synonyms creates the risk of increasing ambiguity. Because of these limitations in the use of key words as query terms and due to the increasing volume of scientific literature, we are prone to miss relevant literature.

Biological network and pathway models are needed to integrate different types of genomic results in a systems biology approach to understand for instance micronutrient health (van Ommen et al., 2008). This approach is currently limited by the quality of the available biological pathways. To improve this, curators integrate knowledge from various scientific domains. Because each domain has specific sets of journals, this means that many journals need to be explored. So in pathway curation the chance of missing important information is thus likewise increased. What we present here is an integrated approach where the pathway content is used to start a text-mining effort, and the results are represented in such a way that they can easily be integrated into the pathway itself by manual curation. In our study we have compiled a text-mining work flow for finding potential pathway entities in the literature for a given context (using Vitamin A and carotenoids as an example). Other researchers have used text mining to build abstract representations of relations in biology. Spasic et al. (2008) have used text-mining solutions to generate a controlled vocabulary of terms, which is a set of relevant words or phrases. In a different study, the text-mining solution generated networks of related concepts (Chen and Sharp, 2004). Our approach is similar to those mentioned above, but differs in the sense that we go one step further. Through a combined representation of the existing pathway and the newly found terms we allow people knowledgeable in the domain under scrutiny to combine already formulated pathway knowledge with textmining results. Thus, offering an integration of automated and manual knowledge collection. In our study, we assessed the relevance of the identified terms in collaboration with domain experts and integrated a number of candidates into the latest pathway representation.

In the present study we apply a semiautomatic approach to identify pathway entities in Medline abstracts. We started with a pathway developed for vitamin A metabolism, which is the best-understood subpathway of the carotenoid pathway (Fig. 1). The text-mining approach was initiated from a single review article with 1,191 references (Balmer and Blomhoff, 2002). In the first step a corpus of Medline abstracts was automatically generated based on these references. This corpus was subsequently analyzed for pathway-related terms. The final output is a ranked list of terms that have been validated by curators for their relevance and novelty to the pathway under scrutiny. Our approach improves the process of generating, enriching and updating pathways.

Methods

Our text-mining solution makes use of the text-mining infrastructure at the European Bioinformatics Institute (EBI) where individual modules solve specific tasks (Whatizit, MedEvi) (Kirsch et al., 2006; Rebholz-Schuhmann et al., 2008). In addition to filtering out pieces of information the solutions also provide explicit links from the identified information to entries in biomedical data resources such as Uniprot (Bairoch et al., 2005), ChEBI (Degtyarenko et al., 2008), and the Human Metabolome Database (Wishart et al., 2007). Uniprot or the Universal Protein Resource, came into existence by merging

[illegible]

Swiss-Prot, TrEMBL, and PIR. ChEBI is database capturing chemical entities active in a biological context, and the Human Metabolome Database contains information of Human endogenous metabolites.

In the first step we generated a seed corpus (SC) from the comprehensive review publication by Balmer and Bloomhoff (2002) that provides 1,191 references (see Fig. 2A). Then we generated a second corpus consisting of a large set of abstracts from Pubmed by using the query “carotenoids” (called “query selected corpus,” QSC, see Fig. 2B). Each abstract from the QSC is assessed for the relevance to our topic by measuring the similarity to the SC (see Fig. 2). The goal was to generate a large set of documents from the scientific literature that contains all relevant documents for the topic, that is, the carotenoid pathway, without imposing any bias on the selection. To this end the documents from the QSC are assessed against the documents from the SC to generate the “similarity extended corpus” (SEC, see Fig. 2C).

For the SC all the titles and abstract texts were combined and processed together, whereas the documents from the QSC were processed individually. First, the sentences in the texts were marked up explicitly, and the part-of-speech information was added to the lemmatized tokens, that is, tokens represented in their dictionary form. Every document was transformed into a vector of its lemmatized tokens after removing noninformative tokens provided from a stop list, and the frequency of the lemmatized tokens in the document was kept to rank the tokens.

1. For each lemmatized term found in a document Dunning's log-likelihood value has been computed. Typically, likelihood values are calculated in the context of hypothesis testing, which follows a binomial distribution; that is, true or false. The values are used to either accept or reject a null-hypothesis. Dunning et al. adapted the log likelihood ratio test to be applicable in a set with multinomial distributions. This adaptation makes the log-likelihood ratio test applicable in automatic text analysis. When counting word occurrences in a document the resulting set follows a multinomial distribution. Dunning's log likelihood value gives an indication if a term is informative in a given context.
2. All terms are ranked according to their log-likelihood values where the highest log-likelihood value obtained is ranked at 1. The ranks are then used to compute the term weight according to the following formula: the inverse of $[1 + \log(\text{rank})]$. This transformation results in a smoother distribution of term weights for a given document.
3. The same procedure is applied to generate the term vector of the SC. Because the SC of the carotenoid pathway contains 1,191 documents, a much larger vector containing the weights of 1,000 terms was used.
4. For each document from the QSC the cosine similarity score is computed between the document's vector and the vector of the SC. Notice that the term weight can be equal to 0 whenever a term that is contained in the SC is not found in the document vector being tested for similarity. The documents from the QSC are ranked according to their decreasing cosine similarity, which indicates their relevance. The best relevant documents are added to the final SEC.

FIG. 2. A two-step text-mining work flow for the enrichment of pathways. During the first phase a corpus of manually assessed abstracts (A) is extended in a semiautomatic manner with abstracts obtained from a high-recall query from PubMed (B). This extended corpus (C) is then input to the second phase in which terms are extracted. The resulting terminology comprises potential pathway concept, which is available to pathway curators to extend a pathway.

5. A random set of abstracts from the QSC ranked according to their similarity score to the SC was evaluated for their relevance to the studied topic. Based on this assessment we derived a threshold for the similarity score. The selection of the threshold for similarity will be explained in detail in the results section. All abstracts with a similarity score higher than the selected threshold were added to the final SEC.

Extracting terminologies containing potential pathway entities

In the next step the documents from the SEC were processed (see Fig. 2C) to deliver a list of statistically significant terms, which are then filtered on relevance to the curated pathway. Potentially novel pathway entities are assumed to belong to the following semantic types: (1) proteins, (2) genes, (3) enzymes, (4) chemical compounds representing metabolites, that is, chemicals being intermediate substances in metabolic processes, and (5) other chemical compounds. Our

analysis was tuned to identify multiword terms in the SEC, because we applied part-of-speech patterns and the mutual information test that measures the association strength between the constituents of multiword terms (Oakes, 1998). Recognition of multiword terms in natural language is complex when the words are not consecutive in a sentence, and this may lead to identification of shorter terms as subconcepts. Presentation of results containing such subconcept to an expert is often enough to make him see the larger picture.

In addition, we estimated the usage patterns for each term from the SEC, such as the evenness of a term's distribution in comparison to its relative frequency in the corpus.

Evenness is measured with the Juillard Dispersion (JD). To this end the corpus is separated into 100 segments, that is, bins containing similar numbers of sentences. Then we compute the frequencies (X_t) of all statistically identified terms in all segments and determined the mean of their frequency over all segments [$X = \text{mean}(X_t)$] and the standard deviation [$S = \text{standard deviation}(X_t, X)$]. The JD is calculated as follows:

$$JD = 100 * (1 - \frac{V}{\sqrt{n-1}}),$$

where ($n = 100$) is the number of segments in the SEC and V is the inverse of the mean of frequencies (X) normalized by the standard deviation (S):

$$V = \frac{S}{X}$$

A high dispersion value $JD(t)$ occurs if a term t is frequent in almost all segments of the corpus. Comparing a term's relative frequency to its dispersion value could be a useful clue in the identification of potentially novel entities due to the following two interpretations:

1. If the term is frequent and has a high dispersion value, then it can be assumed to denote a concept, which is likely to be very important in the context of the pathway represented by the corpus. However, it is likely that such entities have already been included into the pathway representation, because they are mentioned consistently throughout the corpus, and thus were likely to also occur in the documents used to create the initial pathway.
2. If the term is frequent but has a low dispersion value, then this signifies that a term is local to a smaller number of segments of the corpus. Given that we only accept pathway-relevant named entities such as Uniprot entries, metabolites, and other chemical compounds as candidate pathway entity, a combination of high frequency and low dispersion could be indicative of a situation where the term is used in a few abstracts that report on important and new findings related to the pathway. Such entities are more likely to appear as new

suggestions for pathway extension but still have to be evaluated for relevance.

Selecting the SC

In our efforts to develop a suitable text-mining approach for pathway generation we focused on an important part of the carotenoid metabolism, the vitamin A metabolism. The reason for focusing on this part is twofold. It is the best-explored part of the carotenoid pathway, and thus serves as a good benchmark in comparison to less understood pathways, and in addition, the review article by Balmer and Bloomhoff (2002) formed an ideal SCon gene regulation by retinoic acid. This review was an important source of information for the pathway editors from NuGO in that it listed 1,191 articles reporting relevant information to the vitamin A pathway. NuGO is the European Network of Excellence in Nutrigenomics (see <http://www.nugo.org>).

Increasing the recall

We have used the abovementioned 1,191 references as a SC. We extended the SC to 13,579 Medline abstracts by setting the cutoff point for the similarity score at 0.07. The similarity threshold was obtained as a result of an integrated process using the curation capabilities of domain experts and the text processing capabilities of a novel text mining solution. The three following steps were followed:

Step 1: we calculated the similarity score for an increasing number of potentially relevant abstracts (see Fig. 3). The different distributions in Figure 3 depict the similarity scores applied to term vectors of 30, 100, 500, or 1,000 terms, respectively. The introduction of more terms as vector elements decreased the similarity score of initially

FIG. 3. Distribution of similarity scores between a corpus containing potentially relevant publications and a seed corpus. The different graphs depict the difference in distribution for different number of informative terms in simdoc vectors.

better-ranked documents and increased the similarity score of documents at lower ranks. We conclude that the increase of the term vector size leads to an increase in noise (i.e., terms that are not specific to the domain). We select the cutoff point at the value where the increase of terms in the vector leads to a decrease of the ranking for relevant documents and vice versa. This cutoff point was found to be in the range of 15,000 and 20,000 documents with similarity scores between 0.06 and 0.08.

Step 2: three groups of documents were selected that were all represented by term vectors with 1,000 entries (Fig. 3). The first section was picked from the part of the distribution where the term vectors showed high similarity scores (above 0.15). The second part was picked from the region where the different graphs intersect with similarity scores between 0.06 and 0.08. The third part was selected from the tail of the graph, with similarity scores below 0.04. From the first group we selected 20 abstracts with a similarity score just above 0.15. For the second group we selected 20 abstracts with a similarity score around the median value of 0.07 and for the last group 10 abstracts were selected with a similarity score below 0.04 and 10 with a similarity score around 0.01. This evaluation method is known as precision at rank (Trec, 2007).

Step 3: now, all the selected abstracts were presented to the domain experts from NuGO in random order. The abstracts were assessed for their relevance to the studied pathway and based on the evaluation by domain experts, the precision was calculated for each section (Table 1).

The precision in the first section was 100%, 60% in the second, and 15% in the last one (Table 1). This outcome confirms our expectation that the cutoff point should be selected in a range where the similarity score indicates that the term vectors mainly contain relevant terms. We decided to take the median value of the second section, which corresponds to a similarity score of 0.07.

Results

The initial query result on the PubMed query "carotenoids" resulted in a set of 51,628 references of which 34,682 contained an abstract. Of these 34,682 documents 13,579 had a similarity score >0.07, and were considered to be relevant to the construction of the vitamin A metabolism pathway.

Increasing journal coverage

The corpus expansion from 1,129 abstracts to 13,579 abstracts led also to changes in the distribution of journals in the corpus (Fig. 4). By expanding the corpus we observed an increase in the contribution of distinct journals that were not listed in the SC. The extended corpus contained 3,307 distinct journals out of which 2,586 journals were not part of the seed corpus. This clearly shows that the automated corpus expansion has led to larger journal coverage, which is practically not achievable by manual selection of scientific articles.

Extracting the key terminology

From the expanded corpus of 13,579 abstracts, we were able to extract 89,086 unique terms. A term may consist of

TABLE 1. PRECISION AT RANK EVALUATION

Rank	Pubmed Id	Similarity score	Relevant
A			
1141	7141883	0.154899	+
1142	10693163	0.154814	+
1143	1317113	0.154776	+
1144	7486470	0.154721	+
1145	8843984	0.154714	+
1146	9795972	0.154656	+
1147	438897	0.154653	+
1148	8504149	0.154643	+
1149	9212349	0.154601	+
1150	15735074	0.154554	+
1151	16614418	0.154553	+
1152	7346779	0.154543	+
1153	8823154	0.154535	+
1154	9108943	0.154528	+
1155	16365078	0.154524	+
1156	3632216	0.154506	+
1157	8503360	0.154503	+
1158	17234732	0.154502	+
1159	16177187	0.154477	+
1160	10846237	0.154368	+
precision	100%		
B			
16868	12060479	0.060701	+
16615	1309942	0.061302	+
15008	9272132	0.065686	+
15007	16060221	0.065687	+
15006	16688767	0.065687	+
15005	9173086	0.06569	+
14995	17493127	0.065714	+
14994	9720977	0.065715	—
10003	1873990	0.083392	—
10002	14692515	0.083394	+
10001	16232082	0.083396	—
10000	12671093	0.083397	—
9999	3572247	0.08342	—
9998	3107194	0.083421	+
9997	1328400	0.083421	+
9996	11978137	0.083425	+
9995	10932161	0.083435	—
9994	10080695	0.083444	—
9993	10356420	0.083453	+
9992	4424510	0.083459	—
precision	60%		
C			
35926	1169117	0.011403	—
35928	10080118	0.011387	—
35204	15712987	0.015108	—
35203	7107607	0.015114	—
35202	11388477	0.015117	—
35196	7236601	0.015143	—
35151	15564532	0.015391	—
35141	8317903	0.015441	—
35117	11204602	0.015506	—
35111	11978818	0.015533	—
35107	3932288	0.015558	+
25008	15745429	0.04189	—
25007	12110702	0.041894	—
25006	7847852	0.041894	—
25005	12068573	0.0419	+
25004	1791223	0.041903	—
25003	8536624	0.041906	+

(Continued)

TABLE 1. (CONTINUED)

Rank	Pubmed Id	Similarity score	Relevant
25002	7679173	0.041907	—
25001	13679861	0.041911	—
25000	2376553	0.041911	—
precision	15%		

Three sections were picked with relatively high, intermediate, and low similarity scores. The precision was calculated for each section to obtain a threshold for relevance.

multiple words. This extracted terminology contains domain independent terms, because the extraction methods did not impose any domain-specific filter. Examples of domain independent terms are: "Etude du Vieillissement Art," "kg body wt," or "Southwest Oncology Group." This shows that not all statistically significant terms are relevant to the analyzed pathway even though they were extracted from a corpus of relevant abstracts.

From all extracted terms we identified 6,515 potential entities for the vitamin A metabolism pathway. For clarity, we distinguish single-word terms from multiple-word terms. Single-word terms are more likely to be ambiguous than multiword terms. The first assessment of the created terminology was then performed on the multiword terms.

Presenting potential pathway entities in context

We first presented a list of found terms that could be a potential pathway entity, in a html page (see [http://www.bigcat](http://www.bigcat.unimaas.nl/public/data/textmining/carotenoids)

.unimaas.nl/public/data/textmining/carotenoids), where a link to the abstracts from the SEC that contained this term is also presented. The list of abstracts, when opened, shows the sentences containing the concept plus a clickable PubMed identifier to the original publication. This part is primarily meant to verify the textmining results themselves.

To facilitate the contextual evaluation we integrated our newly found entities as a separate list in the carotenoid pathway that is available on WikiPathways.

This allows the curators to use the pathway editors functionality on WikiPathways to review the results, to connect the new entities to the existing pathway, and to add database information to individual concepts, to leave them as a separate list of related entities or to remove them. In general, this mechanism, allows us to integrate results from automated text mining with manual curation.

The final result of our text-mining work flow is a list of terms representing potential pathway entities, which are hyperlinked to their original context of occurrence in the expanded corpus. We have built an interface to browse the terminology (Fig. 5). In this interface the results can be sorted by the JD values and their frequencies. It is also possible to filter for specific semantic types such as enzymes, metabolites, or other chemical compounds.

The terms in Table 2 were selected from the generated vocabulary. They comprised the most informative term, that is, most frequent, highest JD and high frequency but low JD. Table 2 contains those terms that were found with the uniprot filter (Proteins), Table 3 represents the metabolites found with the HMDB filter, and Table 4 contains terms that were

FIG. 4. The journals that had the relative highest increase in contribution to the extended corpus. The increase is measured in z-scores.

Upload a pathway (gpml)	<input type="button" value="Browse..."/>
Corpus	Carotenoids
Number of records	30
☒ Multiple word	☐ single word
Semantic Type	all
Sort by:	JD dispersion
JD < 80	a > 30
<input type="button" value="Submit Query"/>	

Corpus: Carotenoids
Total number of terms: 336

Number of records: 30							<input type="button" value="Submit Query"/>	
Concept	Context	Uniprot-filter	Chemicals filter	JD	a	Annotation	Comments	
vitamins A	• SEC • MedEvi		Metabolite (hmdb)	95.052	3765	Synonym	vitamin A = retinol	
liquid chromatography	• SEC • MedEvi		other chemical or false +	94.595	715	Irrelevant	method of analysis of carotenoids and retinoids	
fatty acids	• SEC • MedEvi		CHEBI:35366	94.05	765			
retinoic acids	• SEC • MedEvi		Metabolite (hmdb)	93.697	6516	Synonym	retinoic acid is a metabolite of retinol, and is the	
high-performance liquid chromatography	• SEC • MedEvi		other chemical or false +	93.679	407	Irrelevant	method of analysis of carotenoids and retinoids	
ascorbic acid	• SEC • MedEvi		Metabolite (hmdb)	92.624	819	Not Sure	chemical name of vitamin C, hydrophilic	

FIG. 5. The extracted terms from the similarity extended corpus is available to pathway curators (<http://www.bigcat.unimaas.nl/public/data/textmining/carotenoids/>). Through this interface one could browse the results by sorting on the frequency of occurrence or the Jullian Dispersion (JD). Furthermore, curators could limit the terms on specific semantic types (i.e., proteins, metabolites, chemical compounds). Curators could also consult the context either by extracting the keywords in conjunction with the sentence where they were extracted from, or by using EBI's MedEvi (<http://www.ebi.ac.uk/Rebholz-srv/MedEvi/>).

identified with the chemical compound filter of Whatizit. These terms were then validated by two curators who were also involved in the creation of the initial pathway (Fig. 1). We provided these terms together with an annotation tool where the curators could classify the potentially new pathway enti-

ties according to a predefined set of classes: (1) already included, (2) hyponym of a term already included, (3) hypernym of a term already included, (4) synonym of a term already included, (5) too generic, (6) irrelevant to the studied pathway, and (7) potential new pathway concept.

TABLE 2. PROTEINS THAT ARE POTENTIAL PATHWAY ENTITIES IN VITAMIN A METABOLISM

Multiword Uniprot entities			
Sorted on Jullians Dispersion (JD)	Sorted on frequency of occurrence (a)	JD < 70 a > 10	Single-word Uniprot entities
alkaline phosphatase	protein kinases	tissue-type	dehydrogenases
cytochromes P450	alkaline phosphatase	plasminogen activator	dehydrogenase
protein kinases	cytochromes P450	Phospholipase A2	transglutaminase
Lipoprotein lipase	Lipoprotein lipase	zeta-carotene	Catalase
prostate-specific antigen	prostate-specific antigen	desaturase	peroxidase
zeta-carotene desaturase	tissue-type plasminogen activator	triglyceride lipase	GNMT
gamma-glutamyl transpeptidase	Phospholipase A2	gamma-glutamyl	thrombin
Phospholipase A2	zeta-carotene desaturase	transpeptidase	ACE
acid phosphatase	triglyceride lipase	acid phosphatase	TPA
cyclin-dependent kinase	gamma-glutamyl transpeptidase		NOS
proteinase K	acid phosphatase		AOX
DNA methyltransferase	aryl hydrocarbon hydroxylase		RetSat
tissue-type plasminogen activator	DNA methyltransferase		synthetase
Cytochrome oxidase	cyclin-dependent kinase		ADH3
triglyceride lipase	MAP kinases		PEPCK
aryl hydrocarbon hydroxylase	proteinase K		trypsin
MAP kinases	Reverse transcriptase		Lipase
tissue plasminogen activator	tissue plasminogen activator		ceruloplasmin
aldose reductase	aldose reductase		lysozyme
glutamic-oxaloacetic transaminase	Cytochrome oxidase		TGase
Reverse transcriptase	glutamic-oxaloacetic transaminas		PKA

TABLE 3. METABOLITES THAT ARE POTENTIAL PATHWAY ENTITIES IN VITAMIN A METABOLISM

<i>Multiword metabolites</i>			
<i>Sorted on Julliards Dispersion (JD)</i>	<i>Sorted on frequency of occurrence (a)</i>	<i>JD < 70 a > 10</i>	<i>Single-word metabolites</i>
vitamins A	retinoic acids	25-hydroxyvitamin D	Retinol
retinoic acids	vitamins A	vitamin D2	beta-carotene
ascorbic acid	Vitamin C	phytanic acid	lycopene
Retinyl palmitate	retinyl ester	lutein esters	lutein
Vitamin C	Retinyl palmitate	nicotinic acid	alpha-tocopherol
retinoic acid	ascorbic acid	L-ascorbic acid	zeaxanthin
<i>all-trans</i> retinoic acids	<i>all-trans</i> -retinoic acids	11- <i>cis</i> retinaldehyde	palmitate
Folic acid	retinoic acid	pantothenic acid	alpha-carotene
<i>all-trans</i> retinol	retinoic acid	ferulic acids	beta-cryptoxanthin
13- <i>cis</i> -retinoic acid	13- <i>cis</i> -retinoic acid	copper ion	astaxanthin
retinyl ester	beta carotenes	alpha carotene	canthaxanthin
<i>all-trans</i> retinoic acid	9- <i>cis</i> -retinoic acids	adenosine	retinal
beta carotenes	Folic acid	monophosphate	Selenium
Linoleic acid	Vitamin D3	chlorogenic acid	Tocopherols
Vitamin D3	<i>all-trans</i> retinol	retinoyl glucuronide	Lycopene
beta carotenes	Linoleic acid	isopentenyl	tocopherol
9- <i>cis</i> -retinoic acids	retinol palmitate	diphosphate	phytoene
reduced glutathione	<i>all-trans</i> retinoic acid	ethanol solution	zinc
Uric acid	Uric acid	glutathione disulfide	cholesterol
retinol palmitate	Vitamin K	caffeic acids	<i>all-trans</i> -retinol
oleic acids	Alpha tocopherol	carnosic acid	retinaldehyde
nitric oxides	<i>all-trans</i> retinoic acid	retinyl ester	gamma-tocopherol
arachidonic acids	beta-carotenes	carbon dioxide	Lutein
<i>all-trans</i> retinoic acid	reduced glutathione	cholesterol sulfate	isotretinoin
docosahexaenoic acids	<i>all-trans</i> beta-carotene	nitrogen dioxide	iron
alpha-tocopherol	arachidonic acids	isopentenyl	cryptoxanthin
Superoxide anion	nitric oxides	pyrophosphate	lutein
Vitamin K	docosahexaenoic acids	alpha-linolenic acid	glutathione
<i>all-trans</i> beta-carotene	oleic acids	13- <i>cis</i> retinoic acids	violaxanthin
	benzoic acids		

Hypernyms are terms denoting more general entities than the term in question, and conversely, hyponyms are terms that are more specific than a given term. For example, lutein is the name of a carotenoid, that is, lutein is the hyponym of a carotenoid and carotenoid is the hypernym of Lutein.

Our initial validation of the 266 potential pathway entities represented in Tables 2, 3 and 4 reduced the list to 36 potential pathway entities for the vitamin A metabolism pathway (Table 5). During this validation the curators not only read the terms themselves, but also the sentences and abstracts in which these potential pathway entities originally occurred. This validation step, based on the text from the Medline abstracts, also resulted in the identification of yet one additional pathway concept (Vitamin D3 receptor) (Heber and Lu, 2002; Torma et al., 1996; Vasarhelyi et al., 1993), which had not been identified by the automatic method, but has been identified by reading the most relevant abstracts. This concept has not been identified automatically because it represents a more complex multiword concept just like vitamin D3 receptor. Although the bigram vitamin D3 was identified by the automatic approach the trigram was not. Taking this additional concept into consideration we had a total of 37 pathway entities that have been identified as result of our semiautomatic extraction methods.

In the next step, the domain experts tried to incorporate the novel entities into the pathway. This processing step led to the result that 12 of the 36 terms and, in addition, the term vitamin

D3 receptor (the 37th term) were found to be pathway entities that had to be included in the pathway for vitamin A metabolism. Fourteen of the remaining 24 entities were attributed to processes of related metabolic pathways like fatty acid metabolism, oxidative stress, coagulation cascade, and cholesterol metabolism. Because such entities form possibly yet unknown links to related pathways, we suggest that text mining not only serves finding new pathway entities but could also have a role in identifying related pathways.

The 10 remaining terms could be categorized either as nutrients or biomarkers. Vitamin A, carotenoids and other pathway concepts are frequently used as biomarkers in clinical and other health studies.

The pathway containing the 13 new pathway entities was given to the expert team on carotenoid metabolism (NuGO focus team). They judged on the relevance of the modifications to the pathway representation and considered the additions as a relevant improvement (Fig. 6).

Discussion

Identification of pathways is ongoing research work. Extraction of pathway-relevant information from the literature, including protein-protein interactions and molecular interactions, is a challenging task. In the current state, curation of involved entities and integration of novel entities into existing pathways is necessary to deliver high-quality resources to the

TABLE 4. CHEMICAL COMPOUNDS THAT ARE POTENTIAL PATHWAY ENTITIES IN VITAMIN A METABOLISM

<i>Multiword chemicals</i>			
<i>Sorted on Julliards Dispersion (JD)</i>	<i>Sorted on frequency of occurrence (a)</i>	<i>JD < 70 a > 10</i>	<i>Single-word chemicals</i>
liquid chromatography	fatty acids	arsenic trioxide	carotenoids
fatty acids	liquid chromatography	phenolic acid	retinoic
high-performance liquid chromatography	retinyl acetates	retinyl phosphate	carotenoid
polyunsaturated fatty acids	high-performance liquid chromatography	unesterified retinol	retinyl
fatty acids	amino acid	Raman spectroscopy	retinoids
retinyl acetates	hepatic vitamin	all-rac-alpha-tocopheryl acetate	retinoid
In spite	polyunsaturated fatty acids	Stanol ester	acid
amino acid	retinol acetate	lipoprotein cholesterol	antioxidant
electron microscopy	double bond	CRBP I	carotene
high-pressure liquid chromatography	fatty acids	25-dihydroxyvitamin D	retinoic
thiobarbituric acid	vitamins B6	acyl coenzyme	<i>all-trans</i> -retinoic
Hepatic vitamin	high-pressure liquid chromatography	heme protein	esters
hydrogen peroxide	phorbol esters	tannic acid	lipid
vitamins B6	cholesteryl ester	retinyl methyl ether	peroxidation
free radical	bile acids	phosphatidyl choline	nutrients
double bond	energy transfer	petroleum ether	9- <i>cis</i>
gel electrophoresis	radical cations	lipoprotein oxidation	provitamin
Retinol acetate	electron microscopy	mitomycin C	pigment
cholesteryl ester	In spite	cytosine arabinoside	ascorbic
Subclinical vitamin	hydrogen peroxide	cyclin E	13- <i>cis</i>
chain reaction	free radical	Eimeria acervulina	micronutrient
Carotenoids Lutein	photosystem II	vitamin K1	retinoids
Gel filtration	thiobarbituric acid	ethyl acetate	13- <i>cis</i> -retinoic
Messenger RNA	Retinol oxidation	redox state	pigments
vitamin B	gel filtration	radical anion	acid
gas chromatography	bile salt	13- <i>cis</i> -4-oxoretinoic acid	oxidation
Actinomycin D	retinyl stearate	Retinyl beta-glucuronide	9- <i>cis</i> -retinoic
steroid hormone	collagen synthesis	11- <i>cis</i> -retinyl palmitate	9- <i>cis</i>
liquid chromatography	chain reaction	6-epoxyretinoic acid	Retinoids
Phorbol esters	subclinical vitamin	Mannosyl retinyl phosphate	xanthophylls

public. In our study, we have semiautomatically produced a list of entities that were finally included into the representation of the carotenoid pathways. Other approaches (Spasic et al., 2008) have tackled the same problem but they have not been evaluated for the integration of novel entities into existing

pathways. Nonetheless, both approaches demonstrate that the scientific literature is still a very rich resource to gather relevant information for the completion of pathway representations.

One crucial step in our analysis is the generation of a corpus that is expanded from the SC and that can be used as input to

TABLE 5. OF THE RETRIEVED TERMS, WHICH WERE ASSESSED AS BEING RELEVANT TO THE VITAMIN A PATHWAY, 12 PROVED TO BE PATHWAY ENTITIES, 13 ARE ENTITIES IN RELATED PATHWAYS AND 10 ARE NOT RELATED BUT WERE IDENTIFIED, BECAUSE THEY ARE ADMINISTERED OR USED AS BIOMARKERS IN CLINICAL STUDIES

<i>New pathway entities</i>	<i>Related processes or pathways</i>	<i>Biomarkers or nutrients</i>
Vitamin D3	linoleic acid	selenium
ADH3	fatty acid	reduced glutathione gamma-tocopherol
alpha-carotene	GNMT	iron
astaxanthin	MAPK	alpha-tocopherol
beta-cryptoxanthin	NOS	zinc
Canthaxanthin	nitric oxides	vitamine B
lutein	oleic acids	vitamin K
lycopene	TGase	vitamine B6 prostate-specific antigen
zeaxanthin	carboxylesterases	
PEPCK	cholesterol	
cryptoxanthin	arachidonic acids	
triglyceride lipase	docosahexaenoic acids	
	tissue-type plasminogen activator	
	aldose reductase	

Title: Retinol metabolism (BiGGat, NuGO)
 Email: susan.coort@bigcat.unimaas.nl
 Organism: Homo sapiens
 Data Source: GenMAPP 2.0

FIG. 6. The resulting pathway of vitamin A metabolism extended with a text-mining approach. The newly included entities are indicated with colored boxes.

the extraction of the key terminology. In our study we have a review containing 1,191 references, which forms an excellent basis for a SC. Often such reviews are not available. In that case, the SC needs to be compiled by consulting experts. The resulting start set can in some cases be extended with references that were added to the studied pathway itself. KEGG and WikiPathways contain such references. This start set can in fact contain reviews like the one we used, which then can, of course, be extended. In other cases Web resources like CiteULike (<http://www.citeulike.org/>) and Connotea (<http://www.connotea.org/>), which provide means for scientists to organize and share references, can be used to find other articles that were often saved in combination with the articles from the start set.

The selection of the extended corpus was based on a scoring function that discriminates between suitable documents and irrelevant documents with an empirically defined cutoff parameter. This distinction is arbitrary to a given extent, but ensures that the best-ranked documents according to the judgment of a domain expert are included in the study.

The main analysis is concerned with the selection of terminology and the assessment of this terminology by domain experts. The overall number of identified entities is small (only 37) in comparison to the overall number of extracted terms (89,086 terms). This reduction step is crucial to the selection of the most relevant terms and to optimize the interaction between the text-mining research group and the team of domain specialist, that is, the amount of relevant terms has to be small enough to be processed by the domain specialists and comprehensive enough to generate sufficient benefits from their work.

The identification of novel terminology from the literature for the completion of pathway representations still requires human assessment to meet the high-quality standards of curated data resources. This will not change in the near future.

On the other side, our study has shown that it is beneficial to consider the whole of Medline for an analysis to search for a small number of relevant terms. It is clear that the initial set of documents that have been selected from a review article did not make reference to all journals that could be relevant to the identification of entities for the selected pathway. In other words, only a text-mining approach that filters information from a large set of documents does not have to rely on assumptions that make a preselection of documents, journals, authors, or keyword queries. Considering the whole of the scientific literature gives advantages in the sense that no restrictions are applied to the primary data resource, and thus one of the many reasons for a bias to the study's results is excluded.

For the future we expect that other research teams will pick up similar approaches to filter the literature for concepts that have to be included into biomedical data resources and ontology's. To some extent, this need will be answered by online search engines that offer efficient access to the scientific literature (Doms and Schroeder, 2005; Kim et al., 2008). In addition, researchers will have to work together with text-mining research teams to identify the most relevant concepts. Altogether, the literature will be filtered many times for different purposes and will disclose step-by-step pieces of information that will be integrated into the public biomedical data resources.

Conclusions and Future Work

The increase in the volume of scientific literature requires new methods for knowledge extraction from the scientific literature. Our approach focused on the carotenoid pathway (retinol metabolism). We generated an extended corpus of Medline abstracts and based on the evaluation of sample sets, we conclude that the final extended corpora contained

additional pathway relevant documents that could only be gathered in a time-consuming manual process otherwise. With the combination of the corpus expansion and the pathway enrichment work flow, we were able to identify 13 relevant and yet uncovered entities that were included into the vitamin A metabolism pathway, which is part of the carotenoid pathway. Our results also show that concept can be identified that are potential links with other processes or pathways. The expanded corpus and the extracted terminology including links to relevant Medline abstracts are available at <http://www.bigcat.unimaas.nl/public/data/textmining/carotenoids/>

The work flow is applicable on other domains. We have also applied it on the extraction of pathways entities of the selenium metabolism pathway. Curators are currently processing the results into extending the existing pathway diagram.

The evaluation of the results of our work flow still requires significant human intervention. With this work flow we were able to select the most important information from much more abstracts than a given number of domain experts would be able to read, interpret, and understand. Essentially, we took the information from 13,579 abstracts preselected both by direct queries and by similarity evaluation with a seed corpus. Moreover, the application of the JD value helps in finding rare entities that are only described in a small part of the selected abstracts. The chance of missing these entities in a manual literature search is high.

We believe that the human intervention is decreased if our work flow is integrated in pathway repositories such as WikiPathways (Pico Ar, 2008). The community then provides the seed corpora. The final result of the work flow is a terminology of potential pathway entities. This could be provided as a list with references to the literature, so that the curators (i.e., the community) can make a well-considered decision on extending the different pathways. To allow integration of this work flow in WikiPathways, we extended this wiki with an interface for automatically generated suggestions.

The pathway is available on the Web page of WikiPathways (Pico Ar, 2008) (<http://www.wikipathways.org>) for download. It can be used for gene expression analyses in Genmapp (Dahlquist et al., 2002) and EU Gene (Cavalieri et al., 2007) and representations of interactions in Cytoscape (Shannon et al., 2003).

Authors' Contributions

A.W., P.P., and D.R.S. conceived and implemented the text-mining work flow. S.C., F.T., and C.E. analyzed the result and provided the expert knowledge for the validation of results. All authors provided content for the final manuscript.

Acknowledgments

This research has been made possible by the close cooperation of five research institutes. We are grateful to the management of these institutes who enabled the researchers to travel and visit each other. In particular, we would like to mention the Netherlands Bioinformatics Community for their support via Biorange Phasar project (SP 4.1.1). Furthermore, we are grateful to the Netherlands Genomics Initiative for their financial support to make Andra Waagmeester 6-month

fellowship and collaborate with the European Bioinformatics Institute in Cambridge (UK). We are also grateful to the European Network of Excellence in Nutrigenomics (NuGO) and its carotenoid focus team for providing a framework from wherein researchers from different scientific domains are able to collaborate.

Author Disclosure Statement

The authors declare that no conflicting financial interests exist.

References

- Amiot-Carlin, M.J. (2008). Plant pigments as bioactive substances. In: *Food Colorants: Chemical and Functional Properties*. (CRC Press, Boca Raton, FL), pp. 127–146.
- Bader, G.D., Cary, M.P., and Sander, C. (2006). Pathguide: a pathway resource list. *Nucleic Acids Res* 34, D504–D506.
- Bairoch, A., Apweiler, R., Wu, C.H., Barker, W.C., Boeckmann, B., Ferro, S., et al. (2005). The Universal Protein Resource (UniProt). *Nucleic Acids Res* 33, D154–D159.
- Balmer, J.E., and Blomhoff, R. (2002). Gene expression regulation by retinoic acid. *J Lipid Res* 43, 1773–1808.
- Bendich, A., and Olson, J.A. (1989). Biological actions of carotenoids. *FASEB J* 3, 1927–1932.
- Cary, M., Bader, G., and Sander, C. (2005). Pathway information for systems biology. *FEBS Lett* 579, 1815–1820.
- Cavalieri, D., Castagnini, C., Toti, S., Maciag, K., Kelder, T., Gambineri, L., et al. (2007). EuGene Analyzer a tool for integrating gene expression data with pathway databases. *Bioinformatics* 23, 2631–2632.
- Chen, H., and Sharp, B.M. (2004). Content-rich biological network constructed by mining PubMed abstracts. *BMC Bioinformatics* 5, 147.
- Dahlquist, K.D., Salomonis, N., Vranizan, K., Lawlor, S.C., and Conklin, B.R. (2002). GenMAPP, a new tool for viewing and analyzing microarray data on biological pathways. *Nat Genet* 31, 19–20.
- Degtyarenko, K., De Matos, P., Ennis, M., Hastings, J., Zbinden, M., McNaught, A., et al. (2008). ChEBI: a database and ontology for chemical entities of biological interest. *Nucleic Acids Res* 36, D344–D350.
- Doms, A., and Schroeder, M. (2005) GoPubMed: exploring PubMed with the Gene Ontology. *Nucleic Acids Res* 33, W783–W786.
- Harrison, E.H. (2005). Mechanisms of digestion and absorption of dietary vitamin A. *Annu Rev Nutr* 25, 87–103.
- Heber, D., and Lu, Q.-Y. (2002). Overview of mechanisms of action of lycopene. *Exp Biol Med* (Maywood) 227, 920–923.
- Jensen, L.J., Saric, J., and Bork, P. (2006). Literature mining for the biologist: from information retrieval to biological discovery. *Nat Rev Genet* 7, 119–129.
- Kim, J.J., Pezik, P., and Rebholz-Schuhmann, D. (2008). MedEvi: retrieving textual evidence of relations between biomedical concepts from Medline. *Bioinformatics* 24, 1410–1412.
- Kirsch, H., Gaudan, S., and Rebholz-Schuhmann, D. (2006). Distributed modules for text annotation and IE applied to the biomedical domain. *Int J Med Inform* 75, 496–500.
- Krinsky, N.I. (1993). Actions of carotenoids in biological systems. *Annu Rev Nutr* 13, 561–587.
- Oakes, M.P. (1998). *Statistics for Corpus Linguistics*. Edinburgh: Edinburgh Textbooks in Empirical Linguistics, Edinburgh University Press.

- Pico Ar, K.T., Van Iersel, M.P., Hanspers, K., Conklin, B.R., and Evelo, C.T. (2008). WikiPathways: Pathway Editing for the People. *PLOS Biol.*
- Rebholz-Schuhmann, D., Arregui, M., Gaudan, S., Kirsch, H., and Jimeno, A. (2008). Text processing through Web services: calling Whatizit. *Bioinformatics* 24, 296–298.
- Shannon, P., Markiel, A., Ozier, O., Baliga, N.S., Wang, J.T., Ramage, D., et al. (2003). Cytoscape: a software environment for integrated models of biomolecular interaction networks. *Genome Res* 13, 2498–2504.
- Shatkay, H., and Feldman, R. (2003). Mining the biomedical literature in the genomic era: an overview. *J Comput Biol* 10, 821–855.
- Spasic, I., Schober, D., Sansone, S.A., Rebholz-Schuhmann, D., Kell, D.B., and Paton, N.W. (2008). Facilitating the development of controlled vocabularies for metabolomics technologies with text mining. *BMC Bioinformatics* 9(Suppl 5), S5.
- TREC. (2007). The Sixteenth Text Retrieval Conference Proceedings.
- Torma, H., Rollman, O., Binderup, L., and Michaelsson, G. (1996). Vitamin D analogs affect the uptake and metabolism of retinol by human epidermal keratinocytes in culture. *J Invest Dermatol Symp Proc* 1, 49–53.
- Van Ommen, B., Fairweather-Tait, S., Freidig, A., Kardinaal, A., Scalbert, A., and Wopereis, S. (2008). A network biology model of micronutrient related health. *Br J Nutr* 99(Suppl 3), S72–S80.
- Vasarhelyi, B., Blazovics, A., and Feher, J. (1993). [The role of vitamin A analogues and derivatives in the regulation of cell function]. *Orv Hetil* 134, 845–848.
- Voutilainen, S., Nurmi, T., Mursu, J., and Rissanen, T.H. (2006). Carotenoids and cardiovascular health. *Am J Clin Nutr* 83, 1265–1271.
- Wishart, D.S., Tzur, D., Knox, C., Eisner, R., Guo, A.C., Young, N., et al. (2007). HMDB: the Human Metabolome Database. *Nucleic Acids Res* 35, D521–D526.
- Yeum, K.J., and Russell, R.M. (2002). Carotenoid bioavailability and bioconversion. *Annu Rev Nutr* 22, 483–504.

Address correspondence to:

Andra Waagmeester

Department of Informatics—BiGCaT

Maastricht University

P.O. Box 616

6200 MD Maastricht, The Netherlands

E-mail: andra.waagmeester@bigcat.unimaas.nl